

**SLx/xRx - Aluminium - Articles**

Material number SLx/xRx

Page: 1 of 8

**1. Product and company identification****Product identifier**

Trade name: SLx/xRx - Aluminium - Articles

**Relevant identified uses of the substance or mixture and uses advised against**General use: Aluminium-Article for orthopedic procedures.  
Reserved for industrial and professional use.**Details of the supplier of the safety data sheet**Company name: Otto Bock Health Care  
Street/POB-No.: 3820 W. Great Lakes Drive  
Postal Code, city: Salt Lake City, UT 84120  
USA

WWW: www.ottobockus.com

Telephone: +1 (801) 956-2400

Telefax: +1 (801) 956-2401

Dept. responsible for information:

Quality Department,  
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time), Email:  
USRegulatory@ottobock.com

Additional information: This safety data sheet pertains to the following products:

13R\*: Tube  
17B\*: Covered Lock Knee Joints, Side bar set, Upper side bar, Lower side bar  
17M10-A: Posterior Free Joints (Aluminium)  
17M21: Aluminium Ring Lock  
2R41=1/2: Tube Adaptor  
2R48: Tube Adaptor, angled  
2R49, 2R50: Tube Adaptor  
2R104, 2R105, 2R106: Modular Transtibial Kit  
2R226, 2R229: SACH Shin Kit  
3R106: Tube Adapter  
4R121=30, 4R121=34: Delta Twist Shock absorber  
7E5: Manual Lock Single Axis Hip Joint  
7E7: Modular Single Axis Hip Joint With Stride Control (Aluminium)  
17M10: Posterior Free Joints (Aluminium)  
SL=AK-32, SL=AK-34, SL=AK-35, SL=AK-36, SL=AK-37: TF Fitting  
SL=LPA-30-XL: TF Fitting, Oval  
SL=LPA-335-XL: Pylon Extension Fitting/Distance Sleeve  
SL=LPA-35: Distance Sleeve  
SL=LPA-35: Pylon Extension Fitting/Distance Sleeve  
SL=LPA-35-L: Pylon Extension Fitting/Distance Sleeve  
SL=LPA-B-30, SL=LPA-B-34: TF Fitting  
SL=RPA-400-30-XL: TF Fitting  
SL=RPA-400-34: Distance Sleeve  
SL=RPA-400-35, SL=RPA-400-35-L, SL=RPA-400-35-XL: Pylon Extension Fitting/Distance Sleeve**Emergency phone number****CHEMTREC, Telephone: +1 (800) 424-9300**

## 2. Hazards identification

### Emergency overview

Appearance: Form: solid, metal parts  
Color: silver gray  
Odor: odorless  
Classification: This material is classified as not hazardous.

### Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

### Hazards not otherwise classified

Processing, e.g. by cutting, sawing or grinding, can produce particles and dust. For risks which have to be observed thereby, see chapter 7: Handling, chapter 8: Exposure controls / personal protection and chapter 11: Toxicology.

Aluminium-dust:

Combustible. Danger of dust explosion. Danger of spontaneous combustion.  
see section 11: Toxicological information

## 3. Composition / Information on ingredients

Chemical characterization: Article of Aluminium-Alloy

## 4. First aid measures

In case of inhalation: In case of troubles after inhalation of dust:  
Move victim to fresh air. Seek medical attention.

Following skin contact: Aluminium-dust: Remove residues with water.  
Change contaminated clothing.

After eye contact: Aluminium-dust: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. In case of troubles or persistent symptoms, consult an ophthalmologist.

After swallowing: Metal parts: Swallowing is not regarded as a possible way of exposition.  
Aluminium-dust: If person is clearly conscious, have them drink two glasses of water to dilute ingested material. Seek medical attention.

### Most important symptoms/effects, acute and delayed

Aluminium-dust: May cause irritations.  
After inhalation of high quantities metallic fume fever may appear.  
Lung damage is possible in a chronic situation.

### Information to physician

Treat symptomatically.

**SLx/xRx - Aluminium - Articles**

Material number SLx/xRx

Page: 3 of 8

## 5. Fire fighting measures

Flash point/flash point range:

no data available

Auto-ignition temperature: no data available

Suitable extinguishing media:

Product is non-combustible. Extinguishing materials should therefore be selected according to surroundings.

Aluminium-dust: Special extinguishing powder for metals.

In case of fire, use dry sand or fire extinguisher of fire class D. Never use water.

Extinguishing media which must not be used for safety reasons:

Aluminium-dust: Never extinguish with a halon or carbon dioxide extinguisher or water.

### Specific hazards arising from the chemical

Aluminium-dust:

Combustible. Danger of dust explosion. Danger of spontaneous combustion.

Aluminium, molten:

After contact with water: Danger of explosion!

## 6. Accidental release measures

Personal precautions: Avoid generation of dust.

In the case of the formation of dust: Wear protective equipment. Do not breathe dust.

Environmental precautions:

Do not allow to penetrate into soil, waterbodies or drains.

Aluminium-dust: Do not empty into drains. (Danger of explosion)

Methods for clean-up: Metal parts/dust:

Take up mechanically, placing in appropriate containers for disposal.

Final cleaning. Avoid generation of dust.

Additional information: Aluminium-dust: Eliminate all ignition sources if safe to do so.

## 7. Handling and storage

### Handling

Advices on safe handling: For mechanical processing:

Avoid respiration of swarf. Wear protective equipment.

Provide adequate ventilation. Keep workplace dry.

If necessary: Use local exhaust.

Precautions against fire and explosion:

For mechanical processing: Avoid generation of dust.

Take precautionary measures against static discharges. Keep away from sources of ignition.

### Storage

Requirements for storerooms and containers:

Keep container dry. Store at room temperature.

**8. Exposure controls / personal protection**

**Exposure guidelines**

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
7429-90-5	SLx/xRx - Aluminium - Articles	USA: ACGIH: TWA	10 mg/m <sup>3</sup>
		USA: ACGIH: TWA	3 mg/m <sup>3</sup>
	Aluminium	USA: OSHA: TWA	15 mg/m <sup>3</sup>
		USA: OSHA: TWA	5 mg/m <sup>3</sup>
	Aluminium	NIOSH: Ceiling	5 mg/m <sup>3</sup>
		USA: ACGIH: TWA	1 mg/m <sup>3</sup>
		USA: NIOSH: TWA	10 mg/m <sup>3</sup>
		USA: NIOSH: TWA	5 mg/m <sup>3</sup>
		USA: OSHA: TWA	15 mg/m <sup>3</sup>
		USA: OSHA: TWA	5 mg/m <sup>3</sup>

**Engineering controls**

Provide adequate ventilation.  
 If necessary: Use local exhaust.  
 See also information in chapter 7, section storage.

**Personal protection equipment (PPE)**

**Eye/face protection** For mechanical processing: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010 or ANSI Z87.1-2003. or face protection shield.

**Skin protection** For mechanical processing: Wear suitable protective clothing.  
 For mechanical processing:  
 Protective gloves according to OSHA Standard - 29 CFR: 1910.138.  
 Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

**Respiratory protection:** For mechanical processing:  
 Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. Particulates filter P2 according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.

**General hygiene considerations:**  
 For mechanical processing:  
 Do not breathe dust.  
 Wash hands before breaks and after work.  
 Provide a conveniently located eye rinse station.

**9. Physical and chemical properties**

**Information on basic physical and chemical properties**

**Appearance:** Form: solid, metal parts  
 Color: silver gray

**Odor:** odorless

**Odor threshold:** no data available

**pH value:** no data available

## SLx/xRx - Aluminium - Articles

Material number SLx/xRx

Page: 5 of 8

Melting point/freezing point:	> 899.6 °F
Initial boiling point and boiling range:	no data available
Flash point/flash point range:	no data available
Evaporation rate:	no data available
Flammability:	no data available
Explosion limits:	no data available
Vapor pressure:	no data available
Vapor density:	no data available
Density:	at 68 °F: $\geq 2.7 \text{ g/cm}^3$
Solubility:	at 68 °F: soluble in mineral acids
Water solubility:	at 68 °F: insoluble
Partition coefficient: n-octanol/water:	no data available
Auto-ignition temperature:	no data available
Thermal decomposition:	no data available
Ignition temperature:	Aluminium-dust: approx. 752 °F

### 10. Stability and reactivity

Reactivity:	no data available
Chemical stability:	Product is stable under normal storage conditions.
Possibility of hazardous reactions	<p>Aluminium-dust:          Combustible. Danger of dust explosion. Danger of spontaneous combustion.</p> <p>Aluminium, molten:          After contact with water: Danger of explosion!</p> <p>Aluminium-dust/water: Danger of bursting of closed cans.</p>
Conditions to avoid:	<p>For mechanical processing:          Keep away from sources of ignition. Protect from moisture contamination.          Take precautionary measures against static discharges.</p>
Incompatible materials:	<p>For mechanical processing:          alcohols, alcali hydroxide, alkali salts, ammonium compounds, halogens, halogenated hydrocarbons, alkalis, nitrates, oxidizing agents, acids, sulfate, sulfides, water.</p> <p>Aluminium-dust: Reacts with water or steam liberating hydrogen and heat.</p>
Thermal decomposition:	no data available

## 11. Toxicological information

### Toxicological tests

Toxicological effects:

- Acute toxicity (oral): Lack of data.
- Acute toxicity (dermal): Lack of data.
- Acute toxicity (inhalative): Lack of data.
- Skin corrosion/irritation: Lack of data.
- Eye damage/irritation: Lack of data.
- Sensitisation to the respiratory tract: Lack of data.
- Skin sensitisation: Lack of data.
- Germ cell mutagenicity/Genotoxicity: Lack of data.
- Carcinogenicity: Lack of data.
- Reproductive toxicity: Lack of data.
- Effects on or via lactation: Lack of data.
- Specific target organ toxicity (single exposure): Lack of data.
- Specific target organ toxicity (repeated exposure): Lack of data.
- Aspiration hazard: Lack of data.

### Symptoms

- In case of inhalation: Aluminium-dust: May cause irritations.
- After inhalation of high quantities metallic fume fever may appear.
- Lung damage is possible in a chronic situation.
- After eye contact: Aluminium-dust: mild irritant

## 12. Ecological information

### Ecotoxicity

Further details: no data available

### Mobility in soil

no data available

### Persistence and degradability

Further details: Methods for the determination of biodegradability are not applicable to inorganic substances.

### Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains.

## 13. Disposal considerations

### Product

Recommendation: Recycling. Refer to manufacturer/supplier for information on recovery/recycling.

**Contaminated packaging**

Recommendation: Dispose of waste according to applicable legislation.  
Completely emptied packages can be recycled.

**14. Transport information**

**USA: Department of Transportation (DOT)**

Proper shipping name: Not restricted

**Sea transport (IMDG)**

Proper shipping name: Not restricted  
Marine pollutant: no

**Air transport (IATA)**

Proper shipping name: Not restricted

**Further information**

No dangerous good in sense of these transport regulations.

**15. Regulatory information**

**National regulations - U.S. Federal Regulations**

Product: Refer to 29 CFR Part 1910 subpart q - Welding, Cutting, Brazing 1910.252.  
Aluminium: TSCA Inventory: listed  
TSCA HPVC: not listed  
Other Environmental Laws:  
SARA Title III Section 313, Toxic Release: Conc. 1.0% / Threshold Standard  
NIOSH Recommendations:  
Occupational Health Guideline: 0022

**National regulations - Great Britain**

Hazchem-Code: -

**16. Other information**

Hazard rating systems:



NFPA Hazard Rating:  
Health: 1 (Slight)  
Fire: 0 (Minimal)  
Reactivity: 0 (Minimal)

HMIS Version III Rating:  
Health: 1 (Slight)  
Flammability: 0 (Minimal)  
Physical Hazard: 0 (Minimal)  
Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	0
PHYSICAL HAZARD	0
X	

Literature: 29 CFR Part 1910 subpart q - Welding, Cutting, Brazing 1910.252

Reason of change: Changes in section 1: Address

Date of first version: 9/10/2008



# SAFETY DATA SHEET

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

## SLx/xRx - Aluminium - Articles

Material number SLx/xRx

Revision date: 3/6/2015

Version: 5

Language: en-US

Date of print: 1/20/2016

Page: 8 of 8

---

### Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.