

3B5-X3 Bionic Prosthetic System

Order Form

Company _____

Practitioner _____

Address _____

Phone _____

Fax _____

Email Address _____

Patient Name _____

Requested Due Date _____

PO Number _____

Shipping Options:

Next Day

Ground

2-Day

Other _____

Prosthesis user

Name _____

Age _____

Gender male female

Weight _____ lbs

Knee center to floor _____ cm

Foot size _____ cm

Color of footshell beige brown

Side of amputation left right

Prosthesis user – Mobility Grade

K Level 3

K Level 4

Amputation level

Transfemoral

Knee Disarticulation

Hip Disarticulation

Bilateral Amputation

Initial Fitting of prosthesis (patient has never been fitted with a prosthesis before).

Follow-up fitting

Current Prosthetic knee joint:

3C98 /3C88 C-Leg®

Serial no. _____

3C96 /3C86 C-Leg® Compact

Serial no. _____

3B1/3B1=ST Genium

Serial no. _____

3B5-X2/3B5-X2=ST

Serial no. _____

Prefitting with another knee joint (Type/Name) _____

3B5-X3 – Bionic Prosthetic System

Knee joint (minimum order quantity: 1)

- qty. **3B5-X3** Bionic Prosthetic System, Pyramid Adapter
- qty. **3B5-X3=ST** Bionic Prosthetic System, Screw Top

includes the following additional components:

757L16-3 AC Adapter, **4E60** Inductive Charger, **4X350-X3** Remote Control

Please select one protector: Included in delivery

- 4X193-1 X3 Cover “**Xtreme**” option
- 4X900 X3 Cover “**Assurance**” option



Electronic Tube Adapter

(minimum order quantity: 1) Included in delivery

- qty. **2R19** Axon Tube Adapter

Recommended Water Proof Feet

- qty. **1C63** Triton Low Profile
- qty. **1C64** Triton Heavy Duty

Recommended Water Proof Components

- qty. **4WR95=1** Lamination Anchor with Pyramid Receiver
- qty. **4WR95=2** Lamination Anchor with Pyramid Adapter
- qty. **4WR95=3** Tube Clamp Adaptor
- qty. **21Y14** Water Resistant Push Valve

Approved Feet

- qty. **1C60** Triton
- qty. **1C61** Triton Vertical Shock (VS)
- qty. **1C62** Triton Harmony®
- qty. **1C31** Trias+
- qty. **1E56** Axtion
- qty. **1E57** Lo Rider
- qty. **1C40** C-Walk
- qty. **1D35** Dynamic Motion

Additional Information for 1E57:

Stiffness: hard medium soft

Impact load/ Activity

- K Level 3: Moderate activity and low impact load
- K Level 3: Moderate activity and moderate impact load
- K Level 4: Moderate activity and high impact load
- K Level 4: High activity and high impact load

Current foot prosthesis (if applicable)

Approved Components

- | | |
|---------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> qty. 4R57 Rotation Adapter | <input type="checkbox"/> qty. 4R84 Double Adapter |
| <input type="checkbox"/> qty. 4R57=ST Rotation Adapter with Thread | <input type="checkbox"/> qty. 4R40 Torsion Adapter |
| <input type="checkbox"/> qty. 4R104=60 Double Adapter, movable | <input type="checkbox"/> qty. 4R118 Adapter Plate |
| <input type="checkbox"/> qty. 4R104=75 Double Adapter, movable | <input type="checkbox"/> qty. 4R43 Lamination Anchor with Threaded Connector (3-prong) |
| <input type="checkbox"/> qty. 4R72=32 Double Adapter | <input type="checkbox"/> qty. 4R89 Lamination Anchor with Pyramid Adapter (3-prong) |
| <input type="checkbox"/> qty. 4R72=45 Double Adapter | <input type="checkbox"/> qty. 4R111=N Lamination Anchor with Threaded Connector (4-prong) |
| <input type="checkbox"/> qty. 4R72=60 Double Adapter | <input type="checkbox"/> qty. 4R111 Lamination Anchor with Pyramid Receiver (4-prong) |
| <input type="checkbox"/> qty. 4R72=75 Double Adapter | |

Accessories

- qty. **60X5** BionicLink PC
- qty. **4X193-1** Additional Xtreme Protective Cover
- qty. **4X900** Additional Assurance Protective Cover