

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: 3/22/2018 Version: 7 Language: en-US Date of print: 5/24/2018

1 of 7

# 616TX1 - ThermoLyn soft/suprasoft (EVA)

Material number 616TX1 Page:

### 1. Product and company identification

#### **Product identifier**

Trade name: 616TX1 - ThermoLyn soft/suprasoft (EVA)

### Relevant identified uses of the substance or mixture and uses advised against

General use: Article for orthopedic procedures.

Processing at Processing temperature and Forming temperature

(refer to section 9: Physical and chemical properties)

Reserved for industrial and professional use.

#### Details of the supplier of the safety data sheet

Company name: Otto Bock Health Care
Street/POB-No.: 3820 W. Great Lakes Drive
Postal Code, city: Salt Lake City, UT 84120

USA

WWW: www.ottobockus.com
Telephone: +1 (801) 956-2400
Telefax: +1 (801) 956-2401

Dept. responsible for information:

Quality Department,

Telephone: +1 (801) 954-2304 (7 AM - 3 PM, Mountain Time),

Email: USRegulatory@ottobock.com

Additional information: This safety data sheet pertains to the following products:

Article No. 616T53: ThermoLyn soft (EVA) Article No. 616T59: ThermoLyn suprasoft (EVA)

Article No. 616T69: ThermoLyn soft, skin-colored (EVA)

Corporate headquarters: Ottobock SE & Co. KGaA Max-Näder-Straße 15

Duderstadt Germany

#### **Emergency phone number**

CHEMTREC, Telephone: +1 (800) 424-9300

### 2. Hazards identification

#### **Emergency overview**

Appearance: Form: solid, plate

Color: Article No. 616T53: colorless Article No. 616T59: colorless

Article No. 616T69: flesh-colored, translucent

Odor: characteristic

Classification: This substance is classified as not hazardous.

#### Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication

Standard (29 CFR 1910.1200) and SIMDUT in Canada.

printed by Otto Bock, Utah with Qualisys SUMDAT



Revision date: 3/22/2018 Version: Date of print: 5/24/2018

2 of 7

#### Hazards not otherwise classified

Processing by heating can produce vapours. Processing, e.g. by cutting, sawing or grinding, can produce particles and dust. For risks which have to be observed thereby, see section 7: Handling, section 8: Exposure controls / personal protection and section 11: Toxicology.

In case of heating: risk of burns. dust/vapors: mild irritant. see section 11: Toxicological information

# 3. Composition / Information on ingredients

Chemical characterization: copolymer based on Ethylene and Vinyl acetate (EVA)

#### 4. First aid measures

For mechanical processing: dust formation. General information:

In case of heating: development of gas/vapor possible.

When vapors form: In case of inhalation:

Provide fresh air. Seek medical treatment in case of troubles.

Remove residues with water. Following skin contact:

If burned by hot product, quench immediately with cold tap water.

Do not peel solidified product off the skin. Immediately get medical attention.

In the case of the formation of dust / When vapors form: After eye contact:

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids

In case of troubles or persistent symptoms, consult an opthalmologist.

#### Most important symptoms/effects, acute and delayed

In case of heating: risk of burns. dust/vapors: mild irritant.

#### Information to physician

Treat symptomatically.

# 5. Fire fighting measures

Flash point/flash point range

> 644 °F

Auto-ignition temperature: 716 - 788 °F (ASTM D1929)

Suitable extinguishing media:

Water spray jet, foam, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

#### Specific hazards arising from the chemical

In case of fire may be liberated: acetic acid-vapors, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

printed by Otto Bock, Utah with Qualisys SUMDAT



in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: 3/22/2018 Version: 7 Language: en-US Date of print: 5/24/2018

3 of 7

# 616TX1 - ThermoLyn soft/suprasoft (EVA)

Material number 616TX1 Page:

6. Accidental release measures

Personal precautions: In case of development of vapors or dust:

Provide fresh air. Do not inhale vapors or dust particles. Wear protective equipment.

Environmental precautions:

Discharge into the environment must be avoided.

Methods for clean-up: Take up mechanically, placing in appropriate containers for disposal.

## 7. Handling and storage

#### Handling

Advices on safe handling: Make sure that the processing machines are well equipped with suction and ventilation

systems.

If necessary: With the formation of dust, use a dust mask.

In case of development of vapors or dust:

Provide fresh air. Do not inhale vapors or dust particles. Wear protective equipment.

Precautions against fire and explosion:

Avoid open flames.

Take precautionary measures against static discharges.

#### Storage

Requirements for storerooms and containers:

Keep only in the original container. Keep container dry.

Protect against direct sunlight.

Keep at temperature not exceeding 122 °F.

# 8. Exposure controls / personal protection

#### **Exposure guidelines**

Occupational exposure limit values:

Туре	Limit value
USA: ACGIH: TWA	10 mg/m³
USA: ACGIH: TWA	3 mg/m³
USA: OSHA: TWA	15 mg/m³
USA: OSHA: TWA	5 mg/m³

#### **Engineering controls**

Provide for constant fresh air supply during and after processing.

See also information in chapter 7, section storage.

#### Personal protection equipment (PPE)

Eye/face protection Tightly sealed safety glasses according to OSHA Standard - 29 CFR: 1910.133 or ANSI

Z87.1-2003.

Skin protection If necessary:

Protective gloves against thermic risks.

For machine processing:

Protective gloves against mechanical risks. OSHA Standard - 29 CFR: 1910.138

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

printed by Otto Bock, Utah with Qualisys SUMDAT



Revision date: 3/22/2018 Version: Date of print: 5/24/2018

4 of 7

Respiratory protection: When vapors form: Respiratory protective device

> For mechanical processing: particulates filter OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2

General hygiene considerations:

The following shall be existing in the immediate working surrounding: emergency shower

installed.

Avoid generation of dust.

Wash hands before breaks and after work.

## 9. Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance: Form: solid, plate

> Color: Article No. 616T53: colorless Article No. 616T59: colorless

Article No. 616T69: flesh-colored, translucent

Odor characteristic No data available Odor threshold:

No data available pH value: Melting point/freezing point: 158 - 212 °F Initial boiling point and boiling range: No data available

> 644 °F Flash point/flash point range:

Evaporation rate: No data available Flammability: No data available No data available **Explosion limits:** No data available Vapor pressure: No data available Vapor density: 0.93 - 0.94 g/cm<sup>3</sup> Density:

Water solubility: insoluble

Partition coefficient: n-octanol/water: No data available

Auto-ignition temperature: 716 - 788 °F (ASTM D1929)

Thermal decomposition: > 200 °C

Additional information: Processing temperature/Forming temperature:

> Article No. 616T53: 160 °C / 320°F Article No. 616T59: 155 °C / 311°F Article No. 616T69: 160 °C / 320°F

# 10. Stability and reactivity

refer to section 10.3 Reactivity:

Chemical stability: Stable under recommended storage conditions.

Maximum storage period (time) 3 year(s)

Possibility of hazardous reactions

No dangerous reactions are known.

Conditions to avoid: Avoid temperatures exceeding Processing temperature °C.

(Processing temperature refer to section 9: Physical and chemical properties)

printed by Otto Bock, Utah with Qualisys SUMDAT



Revision date: 3/22/2018 Version: Date of print: 5/24/2018

5 of 7

Incompatible materials: No data available

Hazardous decomposition products:

In case of fire may be liberated: acetic acid-vapors, carbon monoxide and carbon dioxide.

Thermal decomposition: > 200 °C

# 11. Toxicological information

#### Toxicological tests

Toxicological effects: Acute toxicity (oral): Lack of data.

> Acute toxicity (dermal): Lack of data. Acute toxicity (inhalative): Lack of data. Skin corrosion/irritation: Lack of data.

Serious eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data. Reproductive toxicity: Lack of data. Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data. Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

**Symptoms** 

In case of inhalation: In case of heating: risk of burns. After contact with skin: In case of heating: risk of burns.

After eye contact: dust/vapors: mild irritant

# 12. Ecological information

### **Ecotoxicity**

Further details: No data available

Mobility in soil

No data available

Persistence and degradability

Further details: Product is not biodegradable.

Additional ecological information

Volatile organic compounds (VOC):

0 % by weight

General information: Do not allow to penetrate into soil, waterbodies or drains.

printed by Otto Bock, Utah with Qualisys SUMDAT



in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: 3/22/2018 Version: 7 Language: en-US Date of print: 5/24/2018

6 of 7

# 616TX1 - ThermoLyn soft/suprasoft (EVA)

Material number 616TX1 Page:

13. Disposal considerations

**Product** 

Recommendation: Incinerate according to applicable local, state and federal regulations.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.

Non-contaminated packages may be recycled.

## 14. Transport information

**USA:** Department of Transportation (DOT)

Proper shipping name: Not restricted

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant:

Air transport (IATA)

Proper shipping name: Not restricted

**Further information** 

No dangerous good in sense of these transport regulations.

# 15. Regulatory information

#### National regulations - Great Britain

Hazchem-Code:

### 16. Other information

Hazard rating systems: NFPA Hazard Rating:

0 10

Health: 0 (Minimal)
Fire: 1 (Slight)
Reactivity: 0 (Minimal)
HMIS Version III Rating:
Health: 0 (Minimal)

Flammability: 1 (Slight)
Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

Literature: At processing: See information supplied by the manufacturer.

Reason of change: Changes in section 1.3: Corporate headquarters

Date of first version: 1/9/2008

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

FLAMMABILITY 1
PHYSICAL HAZARD 0
X

printed by Otto Bock, Utah with Qualisys SUMDAT



Revision date: 3/22/2018 Version: Date of print: 5/24/2018

7 of 7

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

with Qualisys SUMDAT printed by Otto Bock, Utah